

# EN 8000

## EN 14492:1 COMPLIANT ELECTRIC WINCH



ARMORTEK ROPE  
AVAILABLE



### INCLUDED



Introducing the latest Winch to our EN range - with a Massive 8000kg (17,637 lbs) pulling power, available in 24v with either Armortek Winch Rope (80ENA24) or Steel Cable (80ENS24). Perfectly suited to Industrial & Commercial applications, this beast can handle whatever you throw at it.

As far as we are aware this is the only genuine 8 Tonne Recovery Winch available that meets the EN14492:1 Standard.

### STANDARD ACCESSORIES

- ⌚ Emergency stop remote handset
- ⌚ Heavy Duty Battery Leads
- ⌚ Isolation Switch
- ⌚ Heavy Duty Roller Fairlead (Or Aluminium)
- ⌚ 13.8mm x 26.5m Steel Cable (Or 14mm x 28m Armortek Winch Rope)

### OUTSTANDING FEATURES

- ⌚ Massive 8000 kg pulling power
- ⌚ Meets the EN14492:1 Standard

## TECHNICAL SPECIFICATIONS

### SPECIFICATION

**RATED LINE PULL:** 8000 kg  
**MOTOR:** 24v : 8.2hp / 6.1kw  
**GEARING:** 450:1  
**DRUM SIZE Dia x L:** 138 x 196mm  
**CABLE Dia x L:** 13.8mm x 26.5m  
**(OR SYNTH ROPE:** 14mm x 28m)  
**MOUNTING PATTERN:** 254 x 114.3mm  
254 x 190.5mm  
**DIMENSIONS:** 635 x 333 x 294mm  
**WEIGHT:** 80 kg

### TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	17637 (8000)
2	14923 (6769)
3	12932 (5866)
4	11408 (5175)

Line pull lbs (kg)	Line Speed 24V ft/min (m/min)	Amps 24v
0	33.8 (10.3)	26
4409 (2000)	11.5 (3.5)	95
8818 (4000)	8.5 (2.6)	140
13228 (6000)	6.6 (2.0)	190
17637 (8000)	5.9 (1.8)	230